

## Gerade Schneidring-Rohrverschraubung aus Edelstahl mit zylindrischem Außengewinde

Temperaturbereich: -40 °C bis +120 °C  
 Werkstoff: Edelstahl 1.4571

Rohr-Außen-Ø	Baureihe	Anschluss	L	SW1	SW2	PN	Artikel-Nr.
6	L	G 1/8 a	23,0	14	14	315 bar	417002
6	L	G 1/4 a	24,5	14	19	315 bar	417004
6	L	G 3/8 a	26,0	14	22	315 bar	417008
6	L	G 1/2 a	26,5	14	27	315 bar	
8	L	G 1/8 a	23,5	17	14	315 bar	417003
8	L	G 1/4 a	25,0	17	19	315 bar	417005
8	L	G 3/8 a	26,0	17	22	315 bar	417009
8	L	G 1/2 a	26,5	17	27	315 bar	417021
10	L	G 1/8 a	26,5	19	17	315 bar	
10	L	G 1/4 a	26,0	19	19	315 bar	417006
10	L	G 3/8 a	27,5	19	22	315 bar	417010
10	L	G 1/2 a	29,0	19	27	315 bar	417013
12	L	G 1/4 a	26,0	22	19	315 bar	417007
12	L	G 3/8 a	27,5	22	22	315 bar	417011
12	L	G 1/2 a	28,0	22	27	315 bar	417014
12	L	G 3/4 a	31,0	22	32	315 bar	417027
15	L	G 3/8 a	28,5	27	24	315 bar	417022
15	L	G 1/2 a	29,0	27	27	315 bar	417015
15	L	G 3/4 a	30,0	27	32	315 bar	417029
18	L	G 3/8 a	31,0	32	27	315 bar	
18	L	G 1/2 a	31,0	32	27	315 bar	
18	L	G 3/4 a	31,0	32	32	315 bar	
22	L	G 1/2 a	33,0	36	32	160 bar	
22	L	G 3/4 a	33,0	36	32	160 bar	
22	L	G 1 a	34,0	36	41	160 bar	
28	L	G 3/4 a	33,0	41	41	160 bar	
28	L	G 1 a	34,0	41	41	160 bar	
28	L	G 1 1/4 a	35,0	41	50	160 bar	
35	L	G 1 a	38,0	50	46	160 bar	
35	L	G 1 1/4 a	39,0	50	50	160 bar	
35	L	G 1 1/2 a	41,0	50	55	160 bar	
42	L	G 1 1/4 a	40,0	60	55	160 bar	
42	L	G 1 1/2 a	42,0	60	55	160 bar	

