


Gerade Schneidring-Rohrverschraubung aus Edelstahl mit Innengewinde

Temperaturbereich: -40 °C bis +120 °C

Werkstoff: Edelstahl 1.4571

Rohr-Außen-Ø	Baureihe	Anschluss	L	SW1	SW2	PN	Artikel-Nr.
6	L	G 1/8 i	34	14	14	315 bar	
6	L	G 1/4 i	39	14	19	315 bar	
8	L	G 1/4 i	39	17	19	315 bar	
10	L	G 1/4 i	40	19	19	315 bar	
10	L	G 3/8 i	41	19	22	315 bar	
12	L	G 3/8 i	41	22	24	315 bar	
12	L	G 1/2 i	41	22	27	315 bar	
15	L	G 1/2 i	46	27	27	315 bar	
18	L	G 1/2 i	47	32	27	315 bar	
22	L	G 3/4 i	52	36	36	160 bar	
28	L	G 1 i	55	41	41	160 bar	
35	L	G 1 1/4 i	63	50	55	160 bar	
42	L	G 1 1/2 i	65	60	60	160 bar	



Gerade Schneidring-Rohrverschraubung aus Edelstahl

Temperaturbereich: -40 °C bis +120 °C

Werkstoff: Edelstahl 1.4571

Rohr-Außen-Ø	Baureihe	L	SW1	SW2	PN	Artikel-Nr.
6	L	39	14	12	315 bar	417032
8	L	40	17	14	315 bar	417033
10	L	42	19	17	315 bar	417034
12	L	43	22	19	315 bar	417035
15	L	46	27	24	315 bar	417036
18	L	48	32	27	315 bar	
22	L	52	36	32	160 bar	
28	L	54	41	41	160 bar	
35	L	63	50	46	160 bar	
42	L	66	60	55	160 bar	