


### Gerade Anschweiß-Rohrverschraubung aus Edelstahl

Temperaturbereich: -40 °C bis +120 °C  
 Werkstoff: Edelstahl 1.4571

Rohr-Außen-Ø	Baureihe	L	D	SW1	SW2	PN	Artikel-Nr.
6	L	29	10	14	12	315 bar	
8	L	31	12	17	14	315 bar	
10	L	33	14	19	17	315 bar	
12	L	33	16	22	19	315 bar	
15	L	37	19	27	22	315 bar	
18	L	40	22	32	27	315 bar	
22	L	45	27	36	32	160 bar	
28	L	47	32	41	41	160 bar	
35	L	54	40	50	46	160 bar	
42	L	58	46	60	55	160 bar	



### Winkel-Schneidring-Rohrverschraubung aus Edelstahl mit Außengewinde

Temperaturbereich: -40 °C bis +120 °C  
 Werkstoff: Edelstahl 1.4571

Rohr-Außen-Ø	Baureihe	Anschluss	L1	L2	SW1	SW2	PN	Artikel-Nr.
6	L	R 1/8 a	26,5	20	14	12	315 bar	417102
6	L	R 1/4 a	26,5	24	14	12	315 bar	417104
8	L	R 1/8 a	28,5	26	17	12	315 bar	417103
8	L	R 1/4 a	28,5	26	17	12	315 bar	417105
8	L	R 3/8 a	29,5	27	17	14	315 bar	417109
8	L	R 1/2 a	31,5	30	17	17	315 bar	417108
10	L	R 1/8 a	30,0	28	19	14	315 bar	
10	L	R 1/4 a	29,5	27	19	14	315 bar	417106
10	L	R 3/8 a	29,5	28	19	14	315 bar	417110
10	L	R 1/2 a	29,5	30	19	19	315 bar	417113
12	L	R 1/4 a	32,0	28	22	17	315 bar	417107
12	L	R 3/8 a	32,0	28	22	17	315 bar	417111
12	L	R 1/2 a	36,0	32	22	19	315 bar	417114
15	L	R 3/8 a	36,0	28	27	19	315 bar	417112
15	L	R 1/2 a	36,0	34	27	19	315 bar	417115
18	L	R 1/2 a	40,0	36	32	24	315 bar	
22	L	G 3/4 a	44,0	42	36	27	160 bar	
28	L	G 1 a	47,0	48	41	36	160 bar	
35	L	G 1 1/4 a	56,0	54	50	41	160 bar	
42	L	G 1 1/2 a	63,0	61	60	50	160 bar	