

SAFETY DATA SHEET

Section 1 – Product & Company Identification

Product Name:
Rechargeable Lithium Ion Batteries, RB-1200 Series

P/N Cells:
US18650VTC5

Product Catalog No.:
55183

Recommended Use:
RIDGID Tools Using RB-1200 Series Batteries

Company Information:

North America

Ridge Tool Company
400 Clark Street
Elyria, Ohio 44035-6001
1-800-519-3456
(8:00 am – 5:00 pm EST, M-F)
Emergency Telephone
call 9-1-1 or local emergency number
www.RIDGID.com

Australia

Ridge Tool Australia
127 Metrolink Circuit
Campbellfield, VIC 3061
1-800-743-443
(8:30 am – 5:00 pm AEST, M-F)
Emergency Telephone
call 000 or local emergency number
www.RIDGID.com.au

Issue Date: January 23, 2017

Section 2 – Hazards Identification

This product is defined as an article per US OSHA 29CFR 1910.1200 (HazCom 2012).

GHS Label Elements: Not applicable

The materials in these Li-Ion batteries are hermetically sealed in a case and do not leak electrolyte under normal usage conditions. However, if exposed to a fire, explosion, extreme abuse, misuse or improper disposal that results in breaching of the battery cell case, hazardous materials may be released. Also, battery terminal contact with other metals may generate heat or cause electrolyte leakage. Electrolyte is flammable. Direct contact with electrolyte may cause severe irritation and chemical burns. Short-term skin exposure may cause chemical burns and sores. Inhalation and injection are not anticipated routes of exposure with leakage of small amounts of electrolyte.

Product Name.....: Rechargeable Lithium Ion Batteries, RB-1200 Series

Section 3 – Composition / Information On Ingredients

Composition:

- Cathode: Lithium nickel cobalt oxides (active material)
Polyvinylidene fluoride (binder)
Carbon black (conductive material)
- Anode: Graphite (active material)
Styrene-butadiene rubber/Carboxymethyl cellulose sodium salt (binder)
- Electrolyte: Organic solvent (non-aqueous liquid)
Lithium salt

Does not contain heavy metals such as mercury, cadmium, lead or chromium

Average Operating Voltage (V)	Rated Capacity	Nominal Capacity
3.6	2500mAh (9.0 Wh)	2600mAh (9.4 Wh)

Section 4 – First Aid Measures

EYE CONTACT:

If contents from an opened battery comes in contact with the eyes, immediately flush eyes thoroughly with water and continue flushing for at least 15 minutes without rubbing. Seek medical attention.

SKIN CONTACT:

If the contents from an opened battery come in contact with the skin, wash with soap and water. If irritation persists or contact has been prolonged, seek medical attention.

INHALATION:

If exposure to fumes or dusts occurs, remove immediately to fresh air and seek medical attention.

INGESTION:

If contents from an opened battery are swallowed, do not induce vomiting. Seek medical attention immediately.

Product Name.....: Rechargeable Lithium Ion Batteries, RB-1200 Series

Section 5 – Fire Fighting Measures

Use specified extinguishers (gas, foam, powder) and extinguishing system under the Fire Defense Law.

Corrosive fumes may be present during fire. Use protective equipment (gloves, breathing apparatus, goggles etc.)

Use a large amount of water as a supportive measure in order to get cooling effect if needed. (Indoor/outdoor fire hydrant).

Carry away flammable materials immediately in case of fire.

Move batteries to a safer place immediately in case of fire.

Section 6 – Accidental Release Measures

PERSONAL PRECAUTIONS:

Use safety gloves and safety goggles, and a gas mask for organic gases when handling leaking battery. Move batteries and contents away from open fire.

ENVIRONMENTAL:

No additional information.

CLEAN-UP MEASURES:

Spills and leaks are unlikely because cells are contained in a hermetically sealed case. If the battery case is breached, wear protective clothing that is impervious to caustic materials and absorb or pack spill residues in inert material.

Section 7 – Handling and Storage

STORAGE:

Store in a cool, well-ventilated location. Prevent condensation on cell or battery terminals. Store within the recommended temperature range of -4°F (-20°C) and 113°F (45°C). Do not expose to temperature above 140°F (60°C). Avoid exposure to static electricity so that no damage will be caused to the protective circuitry of the battery pack. Do not store with metal jewelry, metal covered tables, or metal belts.

Product Name.....: Rechargeable Lithium Ion Batteries, RB-1200 Series

HANDLING:

Accidental short circuit (contacting positive and negative battery terminals with a conductive object) will bring high temperature evaluation to the battery as well as shorter battery life. Be sure to avoid prolonged short circuit since the heat can burn attendant skin and can even rupture the battery cell case. Batteries placed in bulk containers should not be shaken. Metallic objects in tool boxes can cause short circuit. Do not disassemble, remodel, or solder.

CHARGING:

Charge within the limits of 32°F (0°C) and 113°F (45°C). Charge with specified charger designed for this battery. Discharge within the limits of -4°F (-20°C) and 140°F (60°C).

CAUTION: Do not dispose in fire, mix with other battery types, charge above specified rate, connect improperly, or short circuit, which may result in overheating, explosion, or leakage of cell contents.

Section 8 – Exposure Controls / Personal Protection

EXPOSURE GUIDELINES:

Not specified

ENGINEERING CONTROLS:

None required under conditions of normal use. Provide appropriate ventilation in case of electrolyte leakage or exposure.

PERSONAL PROTECTIVE EQUIPMENT:

- **Eye Protection**
None required under conditions of normal use, safety goggles in case of electrolyte leakage.
- **Skin Protection**
None required under conditions of normal use, safety gloves in case of electrolyte leakage.
- **Respiratory Protection**
None required under conditions of normal use, gas mask in case of electrolyte leakage.

Product Name.....: Rechargeable Lithium Ion Batteries, RB-1200 Series

Section 9 – Physical and Chemical Properties

Appearance

Physical State	Sealed Battery
Form	Mostly cylindrical
Color	No data available
Odor	No data available
Odor Threshold	No data available
pH	No data available
Melting point/freezing point	No data available
Initial boiling point and boiling range	No data available
Flash point	No data available
Evaporation rate	No data available
Flammability (solid, gas)	No data available
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%)	No data available
Flammability limit - lower (%)	No data available
Explosive limit – upper (%)	No data available
Explosive limit – lower (%)	No data available
Vapor pressure	No data available
Vapor density	No data available
Relative density	No data available
Solubility(ies)	
Solubility in water	No data available
Solubility (other)	No data available
Partition coefficient (n-octanol/water)	No data available
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Viscosity	No data available

Product Name.....: Rechargeable Lithium Ion Batteries, RB-1200 Series

Section 10 – Stability And Reactivity

STABILITY:

Since batteries utilize a chemical reaction they are considered a chemical product. As such, battery performance will deteriorate over time even if stored for a long period of time without being used. In addition, if the various usage conditions such as charge, discharge, ambient temperature, etc. are not maintained within the specified ranges the life expectancy of the battery may be shortened or the device in which the battery is used may be damaged by electrolyte leakage. The battery is stable under normal operating conditions.

CONDITIONS TO AVOID:

Open flames, heat, sparks and moisture. Battery should not be incinerated, crushed, or abused. Do not subject battery to external short circuit or to temperatures in excess of 140°F (60°C).

INCOMPATIBLE MATERIALS:

No additional information known.

DECOMPOSITION PRODUCTS MAY INCLUDE:

No additional information known.

POSSIBILITY OF HAZARDOUS REACTIONS:

No additional information known

Section 11 – Toxicological Information

ACUTE TOXICITY: No further toxicological data known.

CHRONIC: No further toxicological data known.

SENSITIZATION: No further toxicological data known.

REPRODUCTIVE EFFECTS: No further toxicological data known.

TERATOGENIC EFFECTS: No further toxicological data known.

MUTAGENICITY: No further toxicological data known.

SYNERGISTIC MATERIALS: No further toxicological data known.

CARCINOGENICITY: No further toxicological data known.

Product Name.....: Rechargeable Lithium Ion Batteries, RB-1200 Series

Section 12 – Ecological Information

ECOLOGICAL INFORMATION:

No information available.

Section 13 – Disposal Consideration

WASTE DISPOSAL:

Li-Ion batteries should not be incinerated or subjected to temperatures in excess of 140°F (60°C). Such treatment can cause cell rupture. Isolate positive and negative terminals to avoid touching each other. In the event of disposal, dispose only in accordance with federal, state and local regulations.

These Li-Ion batteries are classified as hazardous waste and are not safe for disposal in the normal waste stream. The Ridge Tool Company encourages recycling, as these batteries do contain recyclable materials that can be reused. The battery packs bear the Rechargeable Battery Recycling Corporation (RBRC) symbol, indicating RIDGID has already paid the cost of recycling the lithium-ion battery packs once they have reached the end of their useful life. For recycling center locations, call 1-800-822-8837.

Section 14 – Transportation Information

UN Number: 3480

Proper Shipping Name: Lithium Ion Batteries

This battery is less than 100WH and has successfully passed UN safety testing. Batteries are packaged in a manner that prevents short circuits and other damage that could lead to failure.

Regulations governing dangerous goods will be relevant when transporting batteries. Follow applicable laws and regulations for transport and disposal.

Special procedures must be followed in the event batteries are damaged, including inspection and repacking. Damaged or defective batteries must not be transported by air.

Product Name.....: Rechargeable Lithium Ion Batteries, RB-1200 Series

Section 15 – Regulatory Information

Check with the appropriate regulatory agencies as regulations may have quantity restrictions, operator variations, or other special provisions

Section 16 – Other Information

Prepared by: Ridge Tool Company (Operating Standard 6-421)

Issue Date: 23 January 2017

Last Revision Date: 23 January 2017

RIDGE TOOL BELIEVES THE STATEMENTS, TECHNICAL INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN ARE RELIABLE BUT THEY ARE GIVEN WITHOUT WARRANTY OR GUARANTEE OF ANY KIND, EXPRESSED OR IMPLIED, AND WE ASSUME NO RESPONSIBILITY FOR ANY LOSS, DAMAGE OR EXPENSE, DIRECT OR CONSEQUENTIAL, ARISING OUT OF THEIR USE.